

L.B.WHITE**PREMIER® DUCTABLE UNIT HEATERS**

	Premier 80	Premier 170	Premier 170 DF	Premier 350	Premier 350 DF
Btu/h Rating					
Maximum	80,000	170,000	170,000	350,000	350,000
Intermediate	-	-	-	175,000	-
Ignition System	Direct Spark	Direct Spark	Direct Spark	Direct Spark	Direct Spark
Heated Air Output (CFM)	450	1200	1200	2400	2400
Dual Fuel Capability:	-	-	Yes	-	Yes
Fuel Consumption (max.)					
Propane (lbs./hr.)	3.7	7.9	7.9	16.2	16.2
Natural Gas (cu.ft./hr.)	80.0	170.0	170.0	350.0	350.0
Inlet Gas Pressure:					
Propane min./max. (in.W.C.)	12.0 / 13.5	11.0 / 13.5	11.0 / 13.5	11.0 / 13.5	11.0 / 13.5
Natural Gas min./max. (in.W.C.)	8.0 / 13.5	7.0 / 13.5	11.0 / 13.5	7.0 / 13.5	11.0 / 13.5
Electrical Supply (Volts / Hz / Phase)	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1
Amps (Starting / Cont. Oper.)	5.0 / 1.5	7.3 / 5.0	7.3 / 5.0	35.0 / 14.0	35.0 / 14.0
Cabinet Material:	Exclusive Tri-shield coating*	Exclusive Tri-shield coating*	Exclusive Tri-shield coating*	Exclusive Tri-shield coating*	Exclusive Tri-shield coating*
Wheels	-	Semi-pneumatic	Semi-pneumatic	Semi-pneumatic	Semi-pneumatic
Fan only mode	S	S	S	S	S
Dimensions (in.)					
Length	30.0	31.0	31.0	48.0	48.0
Width	14.0	18.0	18.0	22.0	22.0
Height	20.0	29.0	29.0	41.0	41.0
Net Weight (lbs.)	81.0	153.0	154.0	295.0	295.0
Shipping Weight (lbs.)	88.0	161.0	162.0	320.0	320.0
Gas Pressure Regulator (with POL)	S	S	S	S	S
Thermostat (Weatherproof with 20' cord)	S	S	S	S	S
Gas Hose	15'	15'	15'	15'	15'
Ducting** (12" or 18" dia. x 12' length)	Gray - 26346 Light Duty - 26348	Gray - 26346 Light Duty - 26348	Gray - 26346 Light Duty - 26348	White - 22835 Light Duty - 24442	White - 22835 Light Duty - 24442
CSA U.S. / Canada Certification:	Yes	Yes	Yes	Yes	Yes

* Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester. S = Standard ** Gray, White, and Light Duty ducts are Optional. Premier 80 and 170 require the 12" diameter duct, and the Premier 350 requires the 18" diameter duct. Part numbers listed. Duct part numbers differ on previously built models. Please call L.B. White for specific part numbers. S = Standard O = Optional



Quality heaters you can count on.

Your L.B. White Dealer:

W6636 L.B. White Rd., Onalaska, WI 54650
 (800) 345-7200
 (608) 783-5691
 (608) 783-6115, fax
 www.lbwhite.com

© 2010 L.B. White Co.
 All rights reserved.
 All specifications are subject
 to change without notice.

F5127.0710