

**L.B.WHITE**

SUN BLAST® TANK TOP RADIANT HEATER

SUN BLAST®	15	30
BTU/H RATING	9,000 / 15,000	9,000 / 30,000
FUEL TYPE	LP	LP
INLET GAS PRESSURE PROPANE MIN./MAX. (IN W.C.)	TANK	TANK
VALVE OUTPUT SETTINGS	LOW/MED/HIGH	LOW/MED/HIGH
OPERATING TIME (20 LB LP CYLINDER)	46 HRS. / 28 HRS.	46 HRS. / 14 HRS.
IGNITION TYPE	MANUAL	MANUAL
LENGTH (IN.)	8.3	6.5
WIDTH (IN.)	7.1	17.3
HEIGHT (IN.)	12.0	15.5
SHIPPING WEIGHT (LBS.)	3.5	6.0
CONTROL VALVE	S	S
EXCESS FLOW VALVE	S	S
SAFETY TIP OVER SWITCH	S	S
PRESET REGULATOR	S	S
POL	S	S
FRONT AND REAR SAFETY GUARDS	S	S
U.S./CANADIAN CERTIFICATION	YES	YES
S=Standard O=Optional	ONE YEAR WARRANTY	



CA RESIDENTS:

 **WARNING**
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

**WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS**

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com

© 2017 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.