

L.B.WHITE**TRADESMAN®
FORCED AIR HEATERS**

TRADESMAN®	125	170	170 ULTRA	170N	170N ULTRA	400	400 ULTRA	400 ULTRA DF
BTU/H RATING	70,000-125,000	125,000-170,000	125,000-170,000	125,000-155,000	125,000-155,000	250,000-400,000	250,000-400,000	175,000-400,000*
HEATED AIR OUTPUT (CFM)	400	550	550	550	550	1,050	1,050	1,050
FUEL TYPE	LP	LP	LP	NG	NG	LP	LP	LP/NG
FUEL CONSUMPTION LP GAS MIN./MAX. (LBS./HR.)	3.2 / 5.8	5.8 / 7.9	5.8 / 7.9	-	-	11.6 / 18.6	11.6 / 18.6	11.6 / 18.6
FUEL CONSUMPTION NAT. GAS MIN./MAX. (CU.FT./HR.)	-	-	-	125 / 155	125 / 155	-	-	175 / 400
INLET GAS PRESSURE LP GAS	11.0 (IN. W.C.)	11.1 (IN. W.C.)	11.1 (IN. W.C.)	-	-	5.2 PSIG	5.2 PSIG	1.5 PSIG
INLET GAS PRESSURE NAT. GAS MIN./MAX.	-	-	-	7/13.5 (IN. W.C.)	7/13.5 (IN. W.C.)	-	-	1.5 PSIG
AMPS (STARTING/CONTINUOUS OPERATION)	2.0 / 0.70	3.7 / 1.0	3.7 / 1.0	3.7 / 1.0	3.7 / 1.0	4.0 / 1.3	4.0 / 1.3	4.0 / 1.3
SERVICE SAVER (SELF-DIAGNOSTICS)	-	-	YES	-	YES	-	YES	YES
LENGTH (IN.)	25.6	24.0	24.0	24.0	24.0	34.5	34.5	34.5
WIDTH (IN.)	11.8	9.5	9.5	9.5	9.5	12.5	12.5	12.5
HEIGHT (IN.)	16.0	16.0	16.0	16.0	16.0	21.5	21.5	21.5
SHIPPING WEIGHT (LBS.)	28.0	34.0	34.0	34.0	34.0	51.0	51.0	55.0
CASE MATERIAL	STEEL W/BAKED ENAMEL	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**	STEEL W/ TRI-SHIELD COATING**
HIGH TEMP SAFETY SWITCH	YES	YES	YES	YES	YES	YES	YES	YES
AIR FLOW SAFETY SWITCH	NO	NO	YES	NO	YES	YES	YES	YES
GAS PRESSURE REGULATOR	S (W/POL)	S (W/POL)	S (W/POL)	S	S	S (W/POL)	S (W/POL)	S (W/POL)
UNIT MOUNT THERMOSTAT	***	S	S	S	S	S	S	S
GAS HOSE	S	S	S	O	O	S	S	S
CSA CERTIFICATION	US & CANADA	US & CANADA	US & CANADA	US & CANADA	US & CANADA	US & CANADA	US & CANADA	US ONLY

S=Standard O=Optional

*250,000 to 400,000 on LP.

** Tri-shield coating consists of 3 unique protective layers: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer, and a baked, thermosetting polyester.

***Thermostat not available due to configuration of gas train.

Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

TWO YEAR WARRANTY

CA RESIDENTS:

Cancer and reproductive harm. See
www.P65Warnings.ca.gov.**WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS**411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.comMADE IN USA
OF U.S. & IMPORTED PARTS© 2017 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.

NEW

MOST COMPACT DUAL FUEL 400,000 BTU/H HEATER ON THE MARKET

L.B.WHITE

**PORTABLE FORCED AIR
TRADESMAN® 400 ULTRA DF**

Lifting Handle

Industrial Strength
Fan Motor

Industry Leading
(2) Year Warranty

3-Trial Ignition
System with
Self Diagnostics

Variable Heat Control and
Thermostat for
Maximum Fuel Efficiency

Tri-Shield Baked
On Enamel Coating
for a Finish That Lasts

Switch Between LP & NG with the
Push of a Level on the DF Unit



COMES WITH:
Regulator and Gas Hose



FEATURES

- Most compact dual fuel 400,000 BTU/H heater on the market
- Weighs only 43 pounds - half the weight of other dual fuel units
- Variable heat output - down to 170,000 BTU/H NG & 250,000 BTU/H LP

Measures 35 inches long.
One foot shorter than other dual fuel units!



Contact your local sales representative
for a demo and more information TODAY!

WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS

CONTRACTOR APPROVED

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com

© 2017 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.