



## VOLT™ ELECTRIC FORCED AIR PORTABLE EVENT HEATER

**L.B.WHITE**

# Convenient, Clean Heat

- ✓ User-friendly electric design
- ✓ For areas where heating & drying is needed
- ✓ Capable of quick, high temp rises
- ✓ Ventilation & air circulation are not needed

### Rental Tough

- Industrial-grade fan
- Stainless jacketed heating coils
- Powder coated steel housing
- High-quality sealed motor

### Safe & Reliable

- Quiet, combustion-free operation
- No fuel spills or odors
- Overheat protection at 104° F
- UL approved



Integrated ambient thermostat  
from 32°F – 100°F

NORTH AMERICAN PROVIDER OF INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650  
(800) 345 7200  
(608) 783 5691  
(608) 783 6115, fax  
[www.lbwhite.com](http://www.lbwhite.com)

© 2025 L.B. White Co.  
All rights reserved.  
All specifications are subject  
to change without notice.



**L.B.WHITE**

## VOLT™ ELECTRIC FORCED AIR PORTABLE EVENT HEATER



VOLT®	1.5	3	6	9	18-1	18-3	40	60
Wattage	1,500	3,000	6,000	9,000 (9kW) 6,000 (6kW)	19,000 (19kW) 13,000 (13kW)	19,000 (19kW) 13,000 (13kW)	40,000 (40kW) 32,000 (32kW) 16,000 (16kW)	60,000 (60kW) 48,000 (48kW) 24,000 (24kW)
BTU/H Rating	5,100	10,200	20,500	30,700 (9kW) 20,500 (6kW)	65,000 (19kW) 45,000 (13kW)	65,000 (19kW) 45,000 (13kW)	136,500 (40kW) 102,400 (32kW) 51,200 (16kW)	205,000 (60kW) 164,000 (48kW) 82,000 (24kW)
Electric supply (volts/Hz/ phase)	120/60/1	240/60/1	240/60/1	240/60/1	240 or 208*/60/1	240 or 208*/60/3	480/60/3	480/60/3
Amps (Starting/ Continuous Operation)	12.5	12.5	25	37.5 (9kW) 25 (6kW)	81 (19kW) 54 (13kW)	47 (19kW) 31 (13kW)	50 (40kW) 40 (32kW) 20 (16kW)	75 (60kW) 60 (48kW) 30 (24kW)
Blower Fan Output (CFM)	116	205	250	350	590 or 1,000	590 or 1,000	1,765	1,765
Power Cord	10ft, 12AWG	10ft, 16AWG	10ft, 8AWG	10ft, 8AWG	Not included	Not included	Not included	Not included
Max Cable Length	N/A	N/A	100-ft (8AWG, 3-wire, SOOW) 100-ft (6AWG, 3-wire, SOOW)	50-ft (8AWG, 3-wire, SOOW) 100-ft (4AWG, 4-wire, SOOW)	50-ft (2AWG, 3-wire, SOOW)	50-ft (6AWG, 4-wire, SOOW) 100-ft (4AWG, 4-wire, SOOW)	50-ft (4AWG, 4-wire, SOOW) 100-ft (2AWG, 4-wire, SOOW)	50-ft (2AWG, 4-wire, SOOW)
Plug	NEMA 5-15P 	NEMA 6-15P 	NEMA 14-30P 	NEMA 14-50P 	Not included	Not included	Not included	Not included
Ambient Thermostat Temperature Range	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F
Length (in.)	11	11	20	23	32	32	46	46
Width (in.)	12	10	12	14	14.5	14.5	20	20
Height (in.)	8	15	17	18	20.5	20.5	25	25
Unit Weight (lbs.)	13.7	20.3	32.9	39.9	62	62	125	125
Shipping Weight (lbs.)	15	22	40	42	65	65	130	130
Running Decibels (dba)	47	50	55	55	58	58	82	82
Three Heat Output Modes	-	-	-	-	S	S	S	S
Powder Coated Steel Housing	S	S	S	S	S	S	S	S
Wheels	-	-	-	-	-	-	S	S
UL Approved	S	S	S	S	S	S	S	-

S=Standard

\* Does not operate at full output

CA RESIDENTS:



Cancer and reproductive harm. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

NORTH AMERICAN PROVIDER OF INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650  
(800) 345 7200  
(608) 783 5691  
(608) 783 6115, fax  
[www.lbwhite.com](http://www.lbwhite.com)

© 2025 L.B. White Co.  
All rights reserved.  
All specifications are subject  
to change without notice.