

L.B.WHITEby **MODINE****GUARDIAN® 2.0 FORCED AIR Horticultural Heating****GUARDIAN® 2.0**

	60	100	250	325
Btu/h Rating:				
Maximum Input	60,000	100,000	250,000	325,000
Minimum Input (variable from)	60,000	50,000 (25,000)	160,000 (65,000)	200,000
Heater Configuration:				
Spark Ignition	—	—	Yes	—
Hot Surface Ignition	Yes	Yes	Yes	Yes
Pilot Ignition	—	—	Yes	—
Fuel Consumption (max.):				
Liquid Propane Gas (lbs./hr.)	2.8	4.6	11.6	15.1
Natural Gas (cu. ft./hr.)	60.0	100.0	250.0	325.0
Heated Air Output (CFM):	240	400	1,050	1,700
Inlet Gas Supply Pressure:				
Propane min./max. (in.W.C.)	11.0 / 13.5	11.0 / 13.5	11.0 / 13.5	11.0 / 13.5
Natural Gas min./max. (in.W.C.)	7.0 / 13.5	7.0 / 13.5	7.0 / 13.5	7.0 / 13.5
Electrical Supply (Volts / Hz / Phase):	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1	240 / 60 / 1
Amps (Starting / Cont. Oper.)				
Spark Ignition	—	—	12.2 / 4.0	—
Hot Surface Ignition	3.3 / 1.0	4.8 / 1.5	12.2 / 4.0	7.1 / 3.2
Pilot Ignition	—	—	7.3 / 4.5	—
Cabinet Material:	Tri-Shield	Tri-Shield	Galvanized*	Galvanized
Dimensions (in.):				
Length	22.5	27.0	30.6	35.0
Width	12.75	14.0	18.0	22.0
Height	18.0	20.0	28.0	30.0
Net Weight (lbs.):	52	67	105	131
Shipping Weight (lbs.):	57	70	126	160
Chain Hanging Kit:	O	O	O	O
Air Diverter:	O	O	O	O
Second Stage Regulator:	O	O	O	O
Thermostat:	O	O	O	O
Sediment Trap:	S	S	S	S
Gas Hose (10ft.):	O	O	O	O
Installation Options:				
Indoor Mount	Yes	Yes	Yes	Yes
Outdoor Mount	Yes	Yes	Yes	Yes
CSA U.S./Canada Certification:	Yes	Yes	Yes	Yes

* Exclusive Tri-shield coating available for AD & AW heaters. Tri-shield coating consists of three unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and a baked, thermosetting polyester.

S = Standard O = Optional

Innovative Climate Solutions

Your L.B. White Dealer:

411 Mason Street
 Onalaska, Wisconsin 54650
 (800) 345-7200 - (608) 783-5691
 (608) 783-6115 fax
 www.lbwhite.com

CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See
www.P65Warnings.ca.gov.