

**L.B.WHITE**

**NEW**

# Mini-T<sup>13</sup>

Radiant Tube Heater

## Benefits/Value:

- 13,000 Btuh
- Ultra low maintenance due to few parts
- Up to 20% energy savings with lower gas usage
- Better heat coverage than traditional brooders
- Variable rate with zone panel
- Easy to clean (power washable)
- Can be hoisted and stored out of the way
- House control available



Comes fully assembled

Easy to hang

Plug and play for current brooders

5 PSI gas pressure

Carbon monoxide output almost undetectable

PATENT PENDING

# Mini-T 13 Radiant Tube Heater Specifications

		Mini-T 13 EC	Mini-T 13
Rating			
- Input (Btuh) Single Stage (max./ min.)		13,000 / (5 psi) 8,000 / (2 psi)	
Tube Length (ft.)		3	
Minimum Installation Height (ft.)		4	
Ignition		Pilot	Manual
Fuel Consumption (max.):			
- Liquid Propane Gas (lbs./hr.)		0.6	
- Natural Gas (cu. ft. / hr.)		13	
Min. Required Ventilation for Heater (CFM)		52	
Inlet Gas Supply Pressure			
- LP Gas min. / max. (in. W.C.)		5.0 / 5.0	
- Natural Gas min. / max. (in. W.C.)		5.0 / 5.0	
Electrical Supply (Volts / Hz / Phase):		120/60/1	NA
Minimum Clearance to Combustibles (in.)	Top	15	
	Sides	12	
	Below Radiant Tubes	36	
Burner Box Material		Stainless Steel	
Reflector Material		Polished Aluminum	
Tube Material		Calorized Steel	
Overall Heater Dimensions (in.)			
- Length		48	
- Width		13-5/8	
- Height		12-1/4	
Net Weight (lbs.)		18	17
Shipping Weight (lbs.)		22	21
1/2" x 6' Gas Hose		0	
Regulator		0	
Gas Cock and Piping Hardware		0	
Hanging Hardware		0	

EC = Electronic Control

PATENT PENDING



**Innovative Climate Solutions**

411 Mason Street, Onalaska, WI 54650  
800 345 7200 (toll free) or 608 783 5691  
608 783 6115 (fax)  
info@lbwhite.com | www.lbwhite.com

Your L.B. White Dealer:



Cancer and reproductive harm. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

© 2024 L.B. White Company  
All rights reserved.  
All specifications are subject to change without notice.