

NEW &
ENHANCED

FOREMAN® 230/500/750 2.0

Indirect-Fired Portable Heater

- ✓ **Reliable BTU** at 500,000 or 750,000 btu/hr
- ✓ **Reliable CFM** with two 12" dia. outlet
- ✓ Foreman 750 is **the lightest weight in its class and only one-person portable 750,000 btu/hr indirect-fired heater on the market**
- ✓ **Quiet operation** at 70 dB or less
- ✓ **Operator-friendly control panel** with:
 - Voltmeter that monitors incoming volts
 - Hour meter that clocks actual runtime (heat mode only)
 - Status and diagnostic lights

NEW Ease of servicing - no belt to maintain

NEW More maneuverable

- Reduction in length
- Reduction in weight

NEW Foreman 750 now 120v

- ✓ **Loaded with options to aid fuel efficiency** including thermostatic control, recirculation mode, and fan-only vent mode
- ✓ **60-gal. fuel tank** (operates as a backup tank on the Foreman 750)
- ✓ **Remote tank connection** that allows for quick switch to backup fuel tank (standard with Foreman 750, optional with Foreman 500)
- ✓ **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- ✓ **Efficient storage options** with no flat wheels and frame that allows for vertical stacking

L.B.WHITE

**L.B.WHITE
LINK**

L.B. White LINK™
Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips. Learn more at LBWhite.com/LINK.

Accessories (Sold Separately)

- Vent Pipe Extension
- Rain Cap
- Regulator for DF model only
- Gas Hose for DF model only
- Duct (12", 16" and/or 20" dia.)
- Duct Adapter (Takes 2 x 12" down to 1 x 16")
- Thermostat with 25 ft cord
- Beckette® GeniSys Contractor Display Tool (For oil model only)
- Stacking Kit



Control Panel:

- Volt Meter
- Hour Meter
- Diagnostic Lights

Thermostatic control option



Easy access rear panel for maintenance and air recirculation option; just add 20" duct



One-person portability



Stackable (kit sold separately)



Two 12" dia. duct up to 100 ft.



One 16" dia. duct up to 100 ft. using duct adapter (sold separately)

Powder-coated protective frame

Single point lifting bale

Fork pockets

NEW &
ENHANCED

FOREMAN® 230/500/750 2.0

Indirect-Fired Portable Heater

L.B.WHITE

®

FOREMAN®	230 DF, 2.0	230 OIL, 2.0	500 DF, 2.0	500 OIL, 2.0	750 DF, 2.0	750 OIL, 2.0
BTU/H RATING	230,000	230,000	500,000	500,000	750,000	750,000
FUEL TYPE	LP/NG	#1 OR #2 DIESEL	LP, NG	#1 OR #2 DIESEL	LP, NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	10.6	--	23.0	--	34.4
	NG (CU.FT./HR)	230	--	500.0	--	750.0
	DIESEL 1 OR 2 (G/HR)	--	1.7	--	3.6	--
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	7/13.5	--	8/13.5	--	8/13.5
	NG (IN W.C.)	7/13.5	--	8/13.5	--	8/13.5
BURNER TYPE	BECKETT®	BECKETT®	RIELLO®	BECKETT®	RIELLO®	BECKETT®
TANK CAPACITY (GALLON)	--	42	--	60	--	60
HEATED AIR OUTPUT (CFM)	1546	1546	2,350	2,350	3,364	3,364
BLOWER FAN (CFM)	1900	1900	3,457	3,457	4,280	4,280
OUTLET STATIC PRESSURE (IN W.C.)	2.5	2.5	2.5	2.5	2.5	2.5
OUTLET DUCT DIAMETER (INCH)	12	12	12X2	12X2	12X2	12X2
RECIRCULATION DUCT DIAMETER (INCH)	16	16	20	20	20	20
MOTOR HORSEPOWER	1/2	1/2	1.0	1.0	1.0	1.0
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1
AMPS (START/CONTINUOUS)	32/9	32/9	60/15	60/16	60/15	60/17
UNIT WEIGHT (LBS)	318	320	617	700	617	700
UNIT LENGTH (IN)	60.2	60.2	84.4	84.4	84.4	84.4
UNIT WIDTH (IN)	26.6	26.6	32.0	32.0	32.0	32.0
UNIT HEIGHT (IN)	43.3	43.3	52.5	52.5	52.5	52.5
SHIP WEIGHT (LBS)*	440	465	785	865	785	865
SHIP LENGTH (IN)	64.0	64.0	88	88	88	88
SHIP WIDTH (IN)	35	35	39	39	39	39
SHIP HEIGHT (IN)	54	54	60	60	60	60
TIGERLOOP OIL DE-AERATOR	S	S	--	0	--	S
LINK™ OPTION	0	0	0	0	0	0
THIRD PARTY CERTIFIED TO ANSI Z83.7/CSA 2.14-2017	YES	YES	YES	YES	YES	YES

TWO YEAR WARRANTY

S=Standard O=Optional

*Ships on custom pallet.

Heaters ship standard to run at 0-2000 feet.
To operate at higher altitudes, please note in order
process to allow for appropriate deviation.



CA RESIDENTS:



Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com



© 2025 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.