



FOREMAN[®] Indirect-Fired Heaters



FOREMAN [®]	230 DF, 2.0	230 Oil, 2.0	500 DF, 2.0	500 Oil, 2.0	750 DF, 2.0	750 Oil, 2.0
Btu/h Rating	230,000	230,000	500,000	500,000	750,000	750,000
Fuel type	LP/NG	#1 or #2 diesel	LP/NG	#1 or #2 diesel	LP/NG	#1 or #2 diesel
Fuel consumption max	LP (lbs./hr)	-	23.0	-	34.4	-
	NG (cu.ft/hr)	-	500.0	-	750.0	-
	Diesel 1 or 2 (g/hr)	-	-	3.6	-	5.4
Inlet gas pressure	LP (in W.C.)	-	8/13.5	-	8/13.5	-
	NG (in W.C.)	-	8/13.5	-	8/13.5	-
Burner type	BECKETT [®]	BECKETT [®]	RIELLO [®]	BECKETT [®]	RIELLO [®]	BECKETT [®]
Tank capacity (gal)	-	42	-	60	-	60
Heated Air output (CFM)	1500	1500	2350	2350	3365	3365
Blower fan output (CFM)	1900	1900	3457	3457	4280	4280
Outlet static pressure (in W.C.)	2.5	2.5	2.5	2.5	2.5	2.5
Motor horsepower	1/2	1/2	1.0	1.0	1.0	1.0
Electrical supply (volts/hz/phase)	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1
Outlet duct diameter (in)	12	12	12	12	12	12
Outlet duct connections	1	1	2**	2**	2**	2**
Outlet duct max length (ft)	100	100	100	100	100	100
Air recirculation inlet dia. (in)	16	16	20	20	20	20
Amps (start/continuous)	32/9	32/9	60/15	60/16	60/15	60/17
Unit length (in)	61	61	84.5	84.5	84.5	84.5
Unit width (in)	33.5	33.5	33.25	33.25	33.25	33.25
Unit height (in)	44.75	44.75	52.5	52.5	52.5	52.5
Unit weight (lbs)	326	363	617	700	617	700
Ship weight (lbs)*	440	460	785	865	785	865
Single point lifting bale	S	S	S	S	S	S
Fork lift pockets	-	-	S	S	S	S
LINK [™] capable	S	S	S	S	S	S
LINK [™] ready	O	O	O	O	O	O
Certified to ANSI/CSA standards	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA

S=Standard O=Optional

*Ships on custom pallet.

Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com
Revised: 2/9/2022

CA RESIDENTS:
 **WARNING**
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

© 2026 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.