



TORCHMAN™/BERTHA™ Torches



TORCHES	Torchman™ SV	Torchman™ 500	Bertha™ 500
BTU/HR rating	300,000	500,000	500,000
Fuel type	LP	LP	LP
Ignition type	Manual	Manual	Manual
Fuel consumption LP gas max (lb/hr)	14.0	23.2	23.2
Fuel consumption NG gas max (cu ft/hr)	-	-	-
Head type	Steel	Steel	Cast iron
Assembled length (in)	29.5	36.0	22.0
Control valve	S	S	S
Excess flow valve	S	S	S
Safety shut-off valve	Yes	-	-
Preset regulator	S	-	O*
POL	S	S	O**
Gas hose (10 f. U.S./15 ft CA)	S	S	S
Thermocouple	S	-	-
Unit weight (lb)	5.2	3.5	7.0
Shipping weight: bulk packed (lb)***	-	-	7.0
Shipping weight: individually packed (lb)	-	-	-
Shipping weight: skin packed (lb)***	8.5	6.0	7.5
Certification	CA	CA	-

S=Standard O=Optional

*Recommended Option

**Included standard with optional regulator assembly

***Bulk Pack sold in packages of 8 torches; Skin packed sold in packages of 4 torches.

CA - Canada model defined by separate configuration.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com
Revised: 2/9/2022

CA RESIDENTS:
 **WARNING**
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

© 2026 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.