



GUARDIAN

	60	100	250	325
Btu/h Rating:				
Maximum Input	60,000	100,000	250,000	325,000
Minimum Input (variable from)	30,000	50,000	160,000	200,000
Heater Configuration:				
Spark Ignition	–	–	Yes	–
Hot Surface Ignition	Yes	Yes	Yes	Yes
Pilot Ignition	–	–	Yes	–
Fuel Consumption (max.):				
Liquid Propane Gas (lbs./hr.)	2.8	4.6	11.6	15.1
Natural Gas (cu. ft./hr.)	60.0	100.0	250.0	325.0
Heated Air Output (CFM):				
	240	400	1,450	1,700
Inlet Gas Supply Pressure:				
Propane min./max. (in.W.C.)				
	11.5 / 13.5	11.5 / 13.5	11.5 / 13.5	11.5 / 13.5
Natural Gas min./max. (in.W.C.)				
	7.0 / 13.5	7.0 / 13.5	7.0 / 13.5	7.0 / 13.5
Electrical Supply (Volts / Hz / Phase):				
Amps (Starting / Cont. Oper.)	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1	220 / 60 / 1
Spark Ignition				
	–	–	3.9 / 2.6	–
Hot Surface Ignition				
	7.0 / 1.1	7.5 / 1.4	11.8 / 4.8	10.5 / 3.5
Pilot Ignition				
	–	–	4.5 / 4.5	–
Cabinet Material:				
	Steel/Tri-Shield	Steel/Tri-Shield	Galvanized	Galvanized
Dimensions (in.):				
Length	21.3	29.5	30.8	36.0
Width	14.3	14.3	18.3	22.0
Height	18.0	18.0	28.3	30.0
Net Weight (lbs.):				
	52	65	116	150
Shipping Weight (lbs.):				
	57	70	126	160
Chain Hanging Kit:				
	O	O	O	O
Air Diverter:				
	O	O	O	O
Second Stage Regulator:				
	O	O	O	O
Thermostat:				
	O	O	O	O
Sediment Trap:				
	S	S	S	S
Gas Hose (10ft.):				
	O	O	O	O
Installation Options:				
Indoor Mount	Yes	Yes	Yes	Yes
Outdoor Mount	Yes	Yes	Yes	Yes
CSA U.S./Canada Certification:				
	Yes	Yes	Yes	Yes

* Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and a baked, thermosetting polyester. S = Standard O = Optional

** Exclusive Tri-shield coating available

Quality heaters you can count on.

Your L.B. White Dealer:

411 Mason Street
 Onalaska, Wisconsin 54650
 (800) 345-7200 - (608) 783-5691
 (608) 783-6115 fax
 www.lbwhite.com

CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See
www.P65Warnings.ca.gov.