

L.B.WHITE

NEW

PREMIER® 700 HEATER

Benefits/Value:

- Flexibility of 700,000 down to 350,000 btu/hr range.
- * Two thermostats provide independent zoning capability.
- Integration of one control panel reducing complexity.
- Convenience of one gas source(Only need to run one gas line).
- Dual Fuel(DF) allows to quickly switch between NG to LP.
- Ducting options:
 - Two 18 inch ducts, provides the ability for two independent zones.
 - One 24 inch duct when using adapter to maximize air flow for one zone.

DF (LP/NG)



* Optional, sold separately

** Certification pending

CA RESIDENTS:

WARNING

Cancer and reproductive harm. See www.P65Warnings.ca.gov.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com

© 2023 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.



PREMIER®	700 DF
BTU/HR rating	700,000/350,000
Heated air output (CFM)	5,000
Fuel type	LP/NG
Fuel consumption LP gas max (lbs/hr)	32.4/16.2
Fuel consumption NG gas max (cu ft/hr)	700/350
Amps (start/continuous)	28/12
Electric supply (volts/hz/phase)	240/60/1
Motor horsepower	1
Running decibels	70.4
Unit length (in)	47.5
Unit width (in)	28.0
Unit height (in)	69.0
Shipping weight (lb)	640
Case material	Tri-Shield™***
Electrical connection	Mounted inlet
Thermostat connection	Mounted inlet
Fork pockets	S
Ventilation (fan only)	S
Mobility kit (500-133766)	O
Gas hose, regulator & thermostat	O
Outlet duct diameter (in)	18
Outlet duct max length (ft)	25
Certified to ANSI/CSA standards	U.S. & CA

S=Standard O=Optional

* Amps spike over 15 during initial start-up. Check breaker capability.

** 18.1 with optional thermostat bracket installed.

*** Tri-shield coated steel with three unique protective layers including: a non-corrosive hot-dipped, galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

Accessories (sold separately):

- 500-133671, 2-1 Outlet adapter for 24" duct
- 500-22835, Duct, 18" x 12' w/ magnetic collar
- 500-133767, Duct, 24" x 25' w/ magnetic collar
- 500-132976, T-Stat with 1.4' cord
- 500-30125, T-Stat with 25' cord
- 574217, Bracket, thermostat holder
- 500-132047, Hose, 1" x 15', 1 NPT both ends
- 500-132136, Regulator, NG
- 500-25141, Regulator, LP
- 500-133766, Mobility Kit

CA RESIDENTS:



Cancer and reproductive harm. See
www.P65Warnings.ca.gov.