

FOREMAN®	750 DF	750 OIL
BTU/H RATING	750,000	750,000
FUEL TYPE	LP, NG	#1 OR #2 DIESEL
FUEL CONSUMPTION LP MAX. (LBS./HR.)	34.5	-
FUEL CONSUMPTION NG MAX. (CU.FT./HR.)	750.0	-
FUEL CONSUMPTION DIESEL 1 OR 2 MAX. (GAL./HR.)	-	5.4
INLET GAS PRESSURE LP MIN./MAX. (IN W.C.)	8/13.5	-
INLET GAS PRESSURE NG MIN./MAX. (IN W.C.)	8/13.5	-
OUTLET STATIC PRESSURE (IN W.C.)	2.5	2.5
VENT STACK DIAMETER (IN.)	6	8
TANK SIZE / OPERATING TIME	-	42 GAL / 8 HRS
BLOWER FAN OUTPUT (CFM)	4,280	4,280
AMPS (STARTING / CONTINUOUS OPERATION)	38/12	38/12
ELECTRIC SUPPLY (VOLTS/HZ/PHASE)	240/60/1	240/60/1
MOTOR HORSEPOWER	2.0	2.0
LENGTH (IN.)	94.0	94.0
WIDTH (IN.)	32.0	32.0
HEIGHT (IN.)	53.0	53.0
SHIPPING WEIGHT (LBS.)	865.0	1021.0
BURNER TYPE	RIELLO	BECKETT
SINGLE POINT LIFTING BALE	S	S
FORK LIFT HOLES	S	S
SELF-DIAGNOSTIC SYSTEM	S	S
TWO 12" OUTLETS*	S	S
20" AIR RECIRCULATION INLET	S	S
U.S./CANADIAN CERTIFICATION	YES	YES
	TWO YEAR WARRANTY	

S=Standard O=Optional

*One 16" air outlet sold separately.



CA RESIDENTS:

WARNING

Cancer and reproductive harm. See www.P65Warnings.ca.gov.

WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS

CONTRACTOR APPROVED

MOST PORTABLE 750,000 BTUH HEATER AVAILABLE

L.B.WHITE

FOREMAN 750® INDIRECT-FIRED HEATER



- Most portable 750,000 BTUH unit available with wheels, fork pockets, and single point lifting bale
- Lightest 750,000 BTUH heater on the market
- 4,280 CFM Blower
- Unique centrifugal fan design for low noise and high air output
- Whisper quiet high performance link belt technology
- Heavy duty ball bearing fan design for long blower life

Contact your local sales representative



recirculation option; just add 20" duct



Uses two 12" ducts standard or one 16" duct (sold seperately).



Farm duty motor





Thermostat (#30125)

(#30902)



Chimney, Raincap (#30161, #30162)

16" Duct Adapter Stacking Kit (#30903)

for a demo and more information TODAY!

WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS