

FOREMAN[®] 230

Indirect-Fired Portable Heater

L.B.WHITE

- ✓ **Highest BTU** in the class at 230,000 btu/hr
- ✓ **Delivers high CFM** with 12" outlet and 16" inlet combination
- ✓ **Operator-friendly control panel** with:
 - Voltmeter that monitors incoming volts
 - Hour meter that clocks actual runtime (heat mode only)
 - Status and diagnostic lights
- ✓ **Aids fuel efficiency** with options to thermostatically control, recirculate, or run in fan-only vent mode
- ✓ **Quiet operation** at 70 dB or less
- ✓ **One-person portability** with telescoping handle
- ✓ **40-gallon tank** for 6 gallons added capacity & +3.5 hours of max runtime (oil model only)
- ✓ **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- ✓ **Two-year warranty**

L.B.WHITE
LINK

L.B. White LINK™
Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.
Learn more at LBWhite.com/LINK.

Accessories (Sold Separately)

Vent Pipe Extension
Rain Cap
Regulator for DF model only
Gas Hose for DF model only
Duct (12" or 16" dia.)
Thermostat with 25 ft cord
Beckett® GeniSys Contractor Display Tool



Powder-coated protective frame

Single point lifting bail

Thermostatic control option

12" dia. duct runs up to 100 ft

Beckett® burner

Clean storage handles

12" no-flat wheels



Control Panel:

- Volt Meter
- Hour Meter
- Diagnostic Lights



Air recirculation option, 16" dia. duct runs up to 25 ft.



One-person portability with telescoping handle

FOREMAN® 230

Indirect-Fired Portable Heater

L.B.WHITE®

FOREMAN®		230 DF	230 OIL
BTU/H RATING		230,000	230,000
FUEL TYPE		LP/NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	10.6	--
	NG (CU.FT/HR)	230	--
	DIESEL 1 OR 2 (G/HR)	--	1.7
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	7/13.5	--
	NG (IN W.C.)	7/13.5	--
BURNER TYPE		BECKETT®	BECKETT®
TANK CAPACITY (GALLON)		--	42
BLOWER FAN OUTPUT (CFM)		1900	1900
OUTLET STATIC PRESSURE (IN W.C.)		2.5	2.5
OUTLET DUCT DIAMETER (INCH)		12	12
RECIRCULATION DUCT DIAMETER (INCH)		16	16
MOTOR HORSEPOWER		1/2	1/2
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)		120/60/1	120/60/1
RUNNING AMPS		9	9
UNIT WEIGHT (LBS)		307	354
UNIT LENGTH (IN)		60.2	60.2
UNIT WIDTH (IN)		26.6	26.6
UNIT HEIGHT (IN)		43.3	43.3
SHIP WEIGHT (LBS)*		421	459
SHIP LENGTH (IN)		64.0	64.0
SHIP WIDTH (IN)		35	35
SHIP HEIGHT (IN)		54	54
LINK™ CAPABLE		S	S
LINK™ READY		0	0
THIRD PARTY CERTIFIED TO ANSI Z83.7/CSA 2.14-2017		YES	YES



CA RESIDENTS:



Cancer and reproductive harm. See www.P65Warnings.ca.gov.

TWO YEAR WARRANTY



S=Standard O=Optional

* Ships on custom pallet

Heaters ship standard to run at 0-2000 feet.
To operate at higher altitudes, please note in order process to allow for appropriate deviation.

INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com

 MADE IN USA
OF U.S. & IMPORTED PARTS

© 2023 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.