

NEW

SUN BLAST® SR 125

Radiant Heater

Stacks for storage
and transportation

Built-in hanging eyes
to free-up floorspace

Heavy-duty body made
from galvanized steel

Easy access
for maintenance

Simple
controls

No electricity? No problem.

- Start & operate without electricity
- 360° heat pattern with furthest throw on the market
- Heats objects like the sun — no heat loss due to air flow

Rental-ready operation & maintenance.

- Easy piezo pilot ignition with manual light option
- Fuel efficient control valve*
- Safe with built-in tilt switch
- Convenient quick-connect hose fittings

* Requires manual adjustment



For more information, visit: lbwhite.com

NEW

SUN BLAST® SR 125

Radiant Heater



| | LP | NG |
|-------------------------|---|---------------------------|
| Modulating Btu/h Rating | 125,000 | |
| Electrical Requirements | ✓ None | |
| Fuel Type | LP | NG |
| Fuel Consumption Max | 5.8 (lbs./hr.) | 125 (cu.ft./hr.) |
| Control Valve | S | |
| Safety Tilt Switch | ✓ | |
| Width (in.) | 16 in. Diameter | |
| Height (in.) | 33 in. | |
| Unit Weight (lbs.) | 28 lbs. | |
| Shipping Weight (lbs.) | 36 lbs. | 35 lbs. |
| Ships With: | 15 ft. Quick-Connect Hose and Regulator | 15 ft. Quick-Connect Hose |
| Warranty | 2 years | |

S=Standard
Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

Certified by:



CA RESIDENTS:
WARNING
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

 MADE IN USA
OF U.S. & IMPORTED PARTS

© 2025 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.

For more information, visit: lbwhite.com