



NORSEMAN™/WORKMAN® Heaters



CONVECTION	WORKMAN® 100N	NORSEMAN™ 200 Plus	WORKMAN® 225	NORSEMAN™ 250
BTU/HR rating	100,000	200,000	45,000-225,000	250,000
Fuel type	NG	LP	LP	LP
Fuel consumption LP gas max (lbs/hr)	-	9.3	2.1 / 10.4	11.6
Fuel consumption NG max (cu ft/hr)	100	-	-	-
Inlet gas pressure LP gas min/max (PSIG)	-	23.0	10.2	23.0
Inlet gas pressure NG min/max (in W.C.)	7.0/13.5	-	-	-
Ignition type	Piezo pilot	Piezo pilot	Piezo	Pilot
Unit length (in)	16.5	18.0	17.0	18.0
Unit width (in)	15.0	13.0	15.0	13.0
Unit height (in)	25.0	24.0	26.0	24.0
Shipping weight (lbs)	14.0	34.0	19.0	34.0
Flame safety	Thermocouple controlled gas valve	Thermocouple controlled gas valve	Thermocouple controlled gas valve	Thermocouple controlled gas valve
Burner type	Stainless steel	Cast iron	Stainless steel	Cast iron
Case material	Galvanized steel	Heavy gauge steel	Galvanized steel	Heavy gauge steel
Gas pressure regulator	S	S	S (w/pol)	S
Gas hose (10 ft U.S./15 ft CA)	O	S	S	S
Certification	U.S. & CA	U.S. & CA	U.S. & CA	*

S=Standard O=Optional

* Norseman™ 250 is L.B. White tested and evaluated, but not third-party certified. Not approved for use on combustible floors.

INNOVATIVE CLIMATE SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com
Revised: 2/9/2022

CA RESIDENTS:
 **WARNING**
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

© 2026 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.