Oval-U 100 Radiant Heater Specifications

Model Numbers	Oval-U 100
Maximum Input (Btu/h):	100,000
Gas Supply Pressure Acceptable for the Purpose of Input Adjustment (in. W.C.) - Propane (max/min) - Natural Gas (max/min)	13.5/11 13.5/7
Fuel Consumption (max.): - Liquid Propane Gas (lbs./hr.) - Natural Gas (cu. ft./hr.)	4.6 100
Ventilation (CFM):	140
Spark Ignition:	Yes
Temperature Controls Available: - Individual Thermostat Control - Wired to House Environmental Control	Yes Yes
Electrical Requirements (Volts / Hz / Phase):	120 / 60 / 1
Minimum Clearance to Combustibles (ft.): - Top - Side - Discharge End - Below Radiant Tubes	.5 3 3 6
Heater Case Dimensions (in.) - Height - Width - Length	13.5 9-13/16 23-5/8"
Overall Heater Dimensions (in.) - Height - Width - Length	13.5 25-3/8 154-1/4
Net Weight (lbs.):	132
Shipping Weight (lbs.):	272
Reflector Material:	Polished Aluminum
Tube Material:	Calorized Steel
3/8" x 6' Gas Hose:	S
Hanging Hardware:	S
Regulator:	0
Piping Hardware, including gas shutoff:	0
Air Inlet Kit	0
Product Warranty	S: 10 years for tube/3 years for burner box
*Shipped in sets of 4	S = Standard O = Optional

PRODUCT WARRANTY

L.B.WHITE

10 year warranty for tubes & **3** year warranty for burner boxes on all Oval-U 100 Radiant Tube Heaters







Innovative Climate Solutions

411 Mason Street, Onalaska, WI 54650 800 345 7200 (toll free) or 608 783 5691 608 783 6115 (fax) info@lbwhite.com | www.lbwhite.com

manuals, maintenance videos, and dealer login access for open orders and recent invoices.

ONLINE RESOURCES

Visit www.lbwhite.com for frequently asked questions, owners

Your L.B. White Dealer:



© 2024 L.B. White Company All rights reserved. All specifications are subject to change without notice.







U-TUBE HEATER WITH OVAL TUBE TECHNOLOGY WIDER HEAT COVERAGE **AND FARTHER HEAT THROW**



Oval-U 100 Radiant Poultry Heaters

Utilizes Already Proven Oval Tube Technology

All the Great Features of the Original Model!



Superior Technology

The Oval-U 100 utilizes L.B. White's **proven oval tube technology.** This unique oval shape gives a more uniform heat pattern, covering the ground better than the competition's models.

Further, with the Oval-U 100's **100% calorized tubes**, you don't have to worry about rusting.










Warmer & Wider Coverage to Floor



135 OFLIR Dist = 3.3 Trefi = 68.0 c = 0.95 75.0 Competitive Unit



800-345-7200 / 608-783-5691 www.lbwhite.com

800-345-7200 / 608-783-5691 www.lbwhite.com