



FOREMAN INDIRECT-FIRED EVENT HEATER

FOREMAN®	500 DF	500 Oil	750 DF	750 Oil
Btu/h Rating	500,000	500,000	750,000	750,000
Fuel Type	LP, NG	Diesel	LP, NG	#1 or #2 diesel
Fuel Consumption LP Max. (lbs./hr.)	23.0	-	34.5	-
Fuel Consumption NG Max. (cu.ft./hr.)	500.0	-	750.0	-
Fuel Consumption Diesel 1 or 2 Max. (gal./hr.)	-	3.6	-	5.4
Inlet gas pressure lp min./max. (in W.C.)	8/13.5	-	8/13.5	-
Inlet gas pressure ng min./max. (in W.C.)	8/13.5	-	8/13.5	-
Outlet static pressure (in w.c.)	1.0	1.0	1.0	2.5
Tank Size / operating time	-	42 gal / 11 hrs	-	42 gal / 11 hrs
Blower Fan Output (CFM)	3,457	3,457	4,280	4,280
Amps (starting / continuous operation)	32.2 / 13.5	32.2 / 13.5	38/12	38/12
Electric Supply (volts/hz/phase)	120/60/1	120/60/1	240/60/1	240/60/1
Motor Horsepower	1.5	1.5	2.0	2.0
Length (in.)	94.0	94.0	94.0	94.0
Width (in.)	32.0	32.0	32.0	32.0
Height (in.)	53.0	53.0	53.0	53.0
Shipping Weight (lbs.)	700.0	850.0	705.0	855.0
Burner type	RIELLO	BECKETT	RIELLO	BECKETT
Single point lifting bale	S	S	S	S
Fork lift holes	S	S	S	S
Self-diagnostic system	S	S	S	S
Two 12" outlets*	S	S	S	S
20" air recirculation inlet	S	S	S	S
U.S./Canadian Certification	yes	yes	yes	yes

TWO YEAR WARRANTY

S=Standard O=Optional
 *One 16" air outlet sold separately.

ACCESSORIES:



Thermostat (#30125)



Chimney, Raincap (#30161, #30162)



16" Duct Adapter (#30902)



Stacking Kit (#30903)

Tested & Listed by **OTL** Part of the L.B. White Group USA
OTL USA
OTL Test Laboratories, Inc.
 Report No: 0545G-H001S (gas)
 Report No: 0545G-H002S (oil)

CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See www.P65Warnings.ca.gov.

WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650
 (800) 345 7200
 (608) 783 5691
 (608) 783 6115, fax
www.lbwhite.com

 **MADE IN USA**
 OF U.S. & IMPORTED PARTS

© 2017 L.B. White Co.
 All rights reserved.
 All specifications are subject to change without notice.